

Transformers

MODEL #	VA RATING	STYLE	OVER CURRENT PROTECTION	CLASS 2	PRIMARY VOLTAGE (VAC)	SEC. VOLTAGE (VAC)	FOOT MOUNT	HUBS	L	W	H	A	B	C	WEIGHT
TR20VA001	20VA	1	Inherent	•	120	24	•	1 Threaded	2.130"	1.890"	2.600"	1.540"	1.625"	0.910"	1.35 lbs.
TR20VA002	20VA	4	Inherent	•	208	24	•	2 Threaded	2.310"	1.890"	2.625"	1.540"	1.625"	1.000"	1.32 lbs.
TR20VA003	20VA	1	Inherent	•	24	24	•	1 Threaded	2.125"	1.890"	2.600"	1.540"	1.625"	0.910"	1.39 lbs.
TR20VA007	20VA	1	Inherent	•	277	24	•	1 Threaded	2.125"	1.890"	2.600"	1.540"	1.625"	0.910"	1.38 lbs.
TR40VA001	40VA	1	Inherent	•	120	24	•	1 Threaded	2.700"	2.200"	2.875"	1.930"	1.750"	1.100"	2.02 lbs.
TR40VA002	40VA	4	Inherent	•	120	24	•	2 Threaded	2.700"	2.200"	2.875"	1.930"	1.750"	1.100"	2.05 lbs.
TR40VA003	40VA	1	Inherent	•	24	24	•	1 Threaded	2.700"	2.200"	2.875"	1.930"	1.750"	1.100"	2.02 lbs.
TR40VA004	40VA	4	Inherent	•	277/240/208/120	24	•	2 Threaded	2.700"	2.200"	2.875"	2.060"	1.750"	1.125"	2.02 lbs.
TR40VA013	40VA	2	Circuit Brkr.	•	480/277/240/208	120	•	1 Threaded	3.293"	2.500"	3.060"	1.873"	1.911"	1.103"	2.65 lbs.
TR40VA015	40VA	1	Internal Thermal	•	240/208/120	24	•	1 Threaded	2.700"	2.200"	2.875"	1.950"	1.750"	1.175"	1.96 lbs.
TR40VA022*	40VA	4	Inherent	•	120	24	•	2 Threaded	2.700"	2.200"	2.875"	1.925"	1.750"	1.100"	2.05 lbs.
TR40VA040^	40VA	9	Internal Thermal	•	240/208/120	24	•	1 Threaded	2.700"	2.200"	2.875"	1.950"	1.750"	1.180"	1.96 lbs.
TR50VA001	50VA	1	Fuse	•	120	24	•	1 Threaded	2.750"	2.200"	2.875"	1.925"	1.750"	1.100"	2.14 lbs.
TR50VA002	50VA	4	Fuse	•	120	24	•	2 Threaded	2.750"	2.200"	2.875"	1.925"	1.750"	1.100"	2.18 lbs.
TR50VA003	50VA	4	Fuse	•	240/208	24	•	2 Threaded	2.750"	2.200"	2.875"	2.000"	1.750"	1.100"	2.17 lbs.
TR50VA004	50VA	5	Circuit Brkr.	•	480/277/240/120	24	•	2 Threaded	3.475"	2.525"	3.000"	1.950"	2.000"	1.200"	3.04 lbs.
TR50VA005	50VA	2	Circuit Brkr.	•	120	24	•	1 Threaded	3.475"	2.525"	3.000"	1.950"	2.000"	1.260"	2.60 lbs.
TR50VA006	50VA	1	Fuse	•	277	24	•	1 Threaded	2.790"	2.200"	2.875"	2.010"	1.750"	1.180"	2.16 lbs.
TR50VA007	50VA	4	Fuse	•	277	24	•	2 Threaded	2.790"	2.200"	2.875"	2.010"	1.750"	1.180"	2.17 lbs.
TR50VA008	50VA	5	Circuit Brkr.	•	480/277/240/208	120	•	2 Threaded	3.475"	2.525"	3.000"	1.950"	2.000"	1.260"	3.04 lbs.
TR50VA009	50VA	5	Circuit Brkr.	•	240/208/120	24	•	2 Threaded	3.475"	2.525"	3.000"	1.950"	2.000"	1.260"	2.82 lbs.
TR50VA014	50VA	2	Circuit Brkr.	•	277	24	•	1 Threaded	3.450"	2.500"	3.050"	1.950"	2.000"	1.260"	2.80 lbs.
TR50VA015	50VA	2	Circuit Brkr.	•	480/277/240/208/120	24	•	1 Threaded	3.475"	2.525"	3.040"	1.950"	2.000"	1.260"	2.98 lbs.
TR50VA016	50VA	2	Circuit Brkr.	•	240/208/120	24	•	1 Threaded	3.475"	2.525"	3.060"	1.950"	2.000"	1.260"	2.90 lbs.
TR50VA017	50VA	2	Circuit Brkr.	•	480/277/208	24	•	1 Threaded	3.475"	2.525"	3.050"	1.950"	2.000"	1.260"	2.86 lbs.
TR50VA018	50VA	13			480/277/240/208	120		1, 90° Conduit Connector, 1 Mounting Plate Opening	Refer to data sheet on website.						3.20 lbs.
TR50VA019*	50VA	11	Inherent	•	277/120	24	•	2 Side Openings	2.310"	2.175"	2.850"	1.857"	1.750"	1.100"	1.99 lbs.
TR75VA001	75VA	2	Circuit Brkr.	•	120	24	•	1 Threaded	3.900"	2.500"	3.000"	2.400"	2.000"	1.625"	3.66 lbs.
TR75VA002	75VA	5	Circuit Brkr.	•	120	24	•	2 Threaded	3.900"	2.500"	3.000"	2.400"	2.000"	1.625"	3.70 lbs.
TR75VA003	75VA	2	Circuit Brkr.	•	277	24	•	1 Threaded	3.875"	2.500"	3.060"	2.400"	2.000"	1.625"	3.60 lbs.
TR75VA004	75VA	6	Circuit Brkr.	•	480/240/208/120	24	•	1 Threaded 1 Side Opening	3.900"	2.500"	3.000"	2.400"	2.000"	1.625"	3.78 lbs.
TR75VA005	75VA	2	Circuit Brkr.	•	480/240/208/120	24	•	1 Threaded	3.900"	2.500"	3.000"	2.400"	2.000"	1.625"	3.62 lbs.
TR75VA007	75VA	5	Circuit Brkr.	•	480/240/208/120	24	•	2 Threaded	3.870"	2.500"	3.060"	2.310"	2.030"	1.670"	3.97 lbs.
TR100VA001	100VA	2	Circuit Brkr.	•	120	24	•	1 Threaded	4.000"	2.500"	3.000"	2.550"	2.000"	1.800"	4.06 lbs.
TR100VA002	100VA	5	Circuit Brkr.	•	120	24	•	2 Threaded	4.000"	2.500"	3.000"	2.550"	2.000"	1.800"	4.13 lbs.
TR100VA002-20*	100VA	5	Circuit Brkr.	•	120	24	•	2 Threaded	4.000"	2.519"	2.992"	2.440"	1.968"	1.850"	4.16 lbs.
TR100VA004	100VA	5	Circuit Brkr.	•	480/277/240/120	24	•	2 Threaded	4.250"	2.500"	3.000"	2.750"	1.975"	2.000"	4.60 lbs.
TR100VA005	100VA	5	Circuit Brkr.	•	480/277/240/120	24	•	1 Threaded	4.270"	2.500"	3.060"	2.699"	2.030"	2.065"	4.74 lbs.
TR100VA008	100VA	5	Circuit Brkr.	•	480/277/240/208	120	•	2 Threaded	4.270"	2.500"	3.060"	2.699"	2.030"	2.065"	4.74 lbs.
TR150VA001	150VA	3	Circuit Brkr.	•	120	24	•	1 Threaded	3.500"	3.790"	3.250"	2.500"	3.225"	1.300"	4.92 lbs.
TR150VA002	150VA	5	Circuit Brkr.	•	120	24	•	2 Threaded	3.620"	3.790"	3.200"	2.600"	3.140"	1.450"	5.29 lbs.
TR150VA008	150VA	12	Circuit Brkr.	•	480/277/240/208	120	•	2 Threaded	4.159"	3.790"	3.200"	2.789"	3.260"	2.087"	4.63 lbs.
TR175VA001	175VA	7			240/208	24	•	2 Bottom Openings	3.800"	3.790"	3.200"	3.000"	3.100"	2.000"	7.05 lbs.
TR175VA002	175VA	4			120	24	•	2 Threaded	3.900"	3.790"	3.175"	3.000"	3.100"	2.000"	7.10 lbs.
TR175VA003	175VA	1	Thermal Fuse on Primary		120	24	•	1 Threaded	4.120"	3.800"	3.200"	3.189"	3.140"	2.087"	7.44 lbs.
TR240VA001	240VA	8			120	24	•	1 Threaded 1 Bottom Opening	3.750"	3.790"	4.500"	3.225"	3.125"	1.800"	9.12 lbs.
TR300VA002	300VA	10	Circuit Brkr.	•	480/240/208/120	24	•	2 End-Bell Openings	5.400"	3.750"	4.500"	3.850"	3.175"	2.500"	12.10 lbs.
TR375VA001	375VA	7			120	24	•	2 Bottom Openings	4.325"	3.790"	4.500"	3.825"	3.150"	2.350"	11.44 lbs.

UL = UL Listed : UL5085-2 or UL5085-3 ; USA & Canada

* = Refer to website for more wire length information.

UR = UL Component Recognized : UL5085-2 or UL5085-3 ; USA & Canada

^ = Dual Terminal Secondary